



FEATURES PP 380X

- Heavy duty, on demand desktop color PassPrinter
- Passport booklet thickness of up to 100 pages
- Direct printing into and on the passport booklets
- Prints on a wide variety of paper based materials
- Flexible Connectivity: USB 2.0 and Ethernet
- User-friendly operating panel
- Optional camera system for layout alignment
- Optional barcode- and OCR reader modules available
- Optional integrated contactless chip reader/writer for ePassports
- ePassport module supports chips up to 72 Kbyte of ISO/IEC 14443 Type A and B

FEATURES PL 60

- High lamination speed and accuracy
- Digital control of lamination speed and temperature
- User-friendly operating panel with LCD display
- Infrared hot-roller heater system
- Power saving due to lower operating temperature and automatic control of speed and temperature

CONFIGURE YOUR ID SYSTEM, ASK FOR:

- EDIsecure® Image Capture Modules
- EDIsecure® Image Enhancement Software
- EDIsecure® Signature Pad
- EDIsecure® Biometric Enrollment Devices
- EDIsecure® Card Management Software Suite
- IDEXpert® ToolACT

For large-scale ID card and passport applications, our software team is able to develop custom workflow management software using the powerful IDEXpert® ProACT. With its state-of-the-art and web-based system platform, users may perform various functions to manage, administer, personalize and encode cards, depending on the rights assigned to them. The system provides configurable interfaces that can be used to connect to multiple data sources or to integrate black list checks and biometric verification.

SPECIFICATIONS OF PP 380X

Media size	Passport booklet up to 100 pages
Resolution	Color 4,800 x 1,200 dpi max.
Print Head	2112 nozzles for black, 2112 nozzles for each color
Printing Time per Datapage	Standard Quality 8 seconds (batch printing) 13 seconds (single printing) High Quality 13 seconds (batch printing) 18 seconds (single printing) Photo Quality 26 seconds (batch printing) 32 seconds (single printing)
Operating System Support	Windows 2000, Windows XP and Windows Vista
Dimensions	500 x 530 x 210 mm (WxDxH)
Weight	approx. 15 kg
Power Supply	100 to 240 V, 50 - 60 Hz / CE
Power Consumption	Printing: 55 W or less Standby: 9 W or less

SPECIFICATIONS OF PL 60

Lamination Method	Thermal transfer
Lamination Speed	0 to 770 mm / min
Lamination Thickness	3.5 mm
Max. Lamination Width	175 mm
Temperature Settings	0 - 160 °C
Dimensions	460 x 270 x 110 mm (WxDxH)
Weight	10 kg
Power Supply	230 V, 50 Hz
Power Consumption	500 W

Digital Identification Solutions AG
Germany
Phone: + 49 711 341 689 - 0
Email: mail@digital-identification.com

Digital Identification Solutions Pte. Ltd.
Singapore 757718
Phone: + 65 6352 8364
Email: mail@sg.digital-identification.com

Digital Identification Solutions (Branch)
Dubai, United Arab Emirates
Phone: + 971 4 299 4146
Email: mail@uae.digital-identification.com

Digital Identification Solutions (Beijing) Co. Ltd.
P.R. China
Phone: + 86 10 6437 4376
Email: mail@cn.digital-identification.com

Digital Identification Solutions S. de R.L. de C.V.
México
Phone: + 52 442 2171 768 - 0
Email: mail@mx.digital-identification.com

Digital Identification Solutions LLC
United States of America
Phone: + 1 864 272 1199
Email: mail@us.digital-identification.com

vps ID Systems GmbH
Germany
Phone: + 49 7243 5488 - 0
Email: info@vps.de



www.digital-identification.com